




SKU Code	Colour	Lumens	Lumens/Watt	Wattage	Beam Angle	Finish Colour	Product Type
AU-ANT1203A/40	4000	2000	80	25	120	Grey	Non Dimmable
AU-ANT1203A/40D	4000	2000	80	25	120	Grey	Dimmable
AU-ANT1203A/40DALI	4000	2000	80	25	120	Grey	DALI Dimmable
AU-ANT1203A/40EM	4000	2000	80	25	120	Grey	Emergency
AU-ANT1203A/40MS	4000	2000	80	25	120	Grey	Microwave
AU-ANT1203A/40MSEM	4000	2000	80	25	120	Grey	Emergency Microwave
AU-ANT1203A/60	6000	2040	82	25	120	Grey	Non Dimmable
AU-ANT1203A/60D	6000	2040		25	120	Grey	Dimmable
AU-ANT1203A/60DALI	6000	2040	82	25	120	Grey	DALI Dimmable
AU-ANT1203A/60EM	6000	2040	82	25	120	Grey	Emergency
AU-ANT1203A/60MS	6000	2040	82	25	120	Grey	Microwave
AU-ANT1203A/60MSEM	6000	2040	82	25	120	Grey	Emergency Microwave

Line Drawing



Polar Curve



Color

Product Features:

- IP65 vandal resistant polycarbonate body and diffuser - ideal for car parks and food preparation areas
- Diffuser permanently attached by two clips for ease of installation
- Gear tray restraints for ease of installation and maintenance
- Optional mounting brackets (included) allow for ceiling, wall or suspended mounting
- Anti-tamper stainless steel clips supplied as standard
- Multiple drill-out conduit entry points at the back and ends of housing
- IK08 impact rating
- Replacement gear trays available - contact sales office for details
- (L70) at a 25,000 hour lifetime
- 3 Year Warranty – see www.auroralighting.com for details
- Adjustable detection range, hold time and lux level settings
- Microwave detection range up to 12 meters.
- Emergency, Microwave and DALI options available

Product Specs:

Input Voltage	220~240V AC
Power Factor	0.95
Number of LEDs	65
Technology	LED
Lifetime L70 (hrs)	25000
IK Rating	IK08
Operating Temp	25°C
Width (mm)	90
Weight (Kg)	1.623
SDCM	4
Positional Adjustment	Fixed

Input Frequency	50/60HZ
Dimmable	No
IP Rating	IP65
Luminaire Distribution	Direct
Dali	Yes
Fire Protection	No
Optic Material	PC
Length (mm)	1274
Positional Adjustment	Fixed
LED Chip	5630

Compliance & Approvals:

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.